

Actual4Labs

Pass Your Next Certification Exam Fast!

Everything you need to prepare, learn & pass your certification exam easily.

Login / Register

Shopping Cart (0)

Search...



Online Test Engine

Instant Online Access, Test History and Performance Review, Supports Windows / Mac / Android / iOS, etc. →

Desktop Test Engine

Installable Software Application, Simulates Real Exam Environment, Supports MS Operating System, Practice Offline Anytime. →

PDF Format

Printable PDF Format, Prepared by IT Experts, Study Anywhere, Anytime, Free PDF Demo Available. →

Choose the version that fits your needs	PDF Version	Desktop Test Engine	Online Test Engine
Latest and Up-to-Date exam dumps with real exam questions answers.	✓	✓	✓
Get 12-Months free updates without any extra charges.	✓	✓	✓
Experience same exam environment before appearing in the certification exam.	✗	✓	✓
100% exam passing guarantee in the first attempt.	✓	✓	✓
20% discount on more than one license and 30% discount on 5+ license purchases.	✗	✓	✓
100% secure purchase on SSL.	✓	✓	✓
Completely private purchase without sharing your personal info with anyone.	✓	✓	✓

<http://www.actual4labs.com>

Excellent Quality Exam Dumps Questions Never Let You down -
Actual4Labs

Exam : 920-111

Title : NCSS-VoIP Communication
Server(CS)2100

Vendors : Nortel

Version : DEMO

NO.1 There are two tables in the call processing application that require datafill before the components in

the LAN can communicate with the Call Agent. One is Table IPHOST, what is the other?

- A. Table IPINV
- B. Table NETINV
- C. Table SERVINV
- D. Table IPNETWRK

Answer: D

NO.2 In the CS 2000 Management Tools, you are about to apply a patch. If the SpApp check box is checked,

what must you do before applying the patch?

- A. Don't do anything. Apply the patch.
- B. Uncheck the check box before continuing.
- C. Display the Special Application instructions before continuing.
- D. Check for the availability of Spare Application cards before continuing.

Answer: C

NO.3 You need to access the Application Launch Point for the SAM21 Shelf Controller Manager. After you

launch a web browser to the following link: http://<host>, what do you input for <host>?

- A. the SAM21 Network Element
- B. the IP address of the Mate Controller
- C. the IP address of the SAM21 Shelf Controller
- D. the name or IP address of the CS 2000 Management Tools Server

Answer: D

NO.4 What do the items displayed on the SAM21 Shelf Controller Manager Network Element display

represent?

- A. a SAM21 Shelf
- B. a CS 2100 XA-Core System
- C. a CS 2100 Compact System
- D. a SAM21 Shelf Controller Card

Answer:A

NO.5 You need to reconfigure the IP addresses of both Call Agent cards in a CS 2100 Compact system. You

have the following base-eight consecutive IP address range for the two Call Agents:

142.68.156.25

142.68.156.26

142.68.156.27

142.68.156.28

142.68.156.29

142.68.156.30

142.68.156.31

142.68.156.32

In the base-eight IP address range, which one must you assign as ACTIVEIRM?

A. 142.68.156.25

B. 142.68.156.26

C. 142.68.156.31

D. 142.68.156.32

Answer: D

NO.6 From the STORM Manager Storage Panel window, when should you execute removal of a file system?

A. after regular working hours

B. after testing file system integrity

C. only at the direction of Nortel support personnel

D. when file systems can be safely removed at any time without effecting the operation

Answer: C

NO.7 Which management system is used as an Application Launch Point to access the SAM21 Shelf

Controller Manager?

A. Call Agent Management (CAM) System

B. CS 2100 Element Manager Web Server

C. Network Patch Management (NPM) System

D. Succession Element and Sub-element Management (SESM) System

Answer: D

NO.8 Nortel recommends an IP addressing scheme for Call Agent and other call processing nodes in the

Communication Server LAN (CS-LAN). Given this information, which manner should you use to provision

the nodes in a CS 2100 Compact Server solution?

- A. in a predetermined Class A address network
- B. in a private call processing subnet of the CS-LAN
- C. in the widely known IP address range of 192.168.0.x
- D. each node is provisioned within its own special subnet of the CS-LAN

Answer: B

NO.9 The Gateway Controller (GWC) requires information so that it can communicate with Call Agent. When

a GWC is added using the CS 2100 Management Tool, an IP address is entered in the Message Router

IP field. What does this IP address belong to?

- A. the Local PTP IP address
- B. the Mate Port 0 IP address
- C. the Local Port 0 IP address
- D. the Call Agentactive IRM IP address

Answer: D

NO.10 A privateLAN is established between two Call Agent cards and uses the 192.168.1.0 network in a CS

2100 Compact Server system. Which ports on the two Call Agent cards use this network?

- A. localptp and mateptp
- B. localport0 and mateport0
- C. localport1 and mateport1
- D. localblade and mateblade

Answer:A